

What is claimed is:

1. A method for measuring an indication of attributes of materials containing a fluid state, the method comprising the steps of:

- 5 providing a time-domain signal indicative of attributes of said materials in a single measurement;

constructing a time-domain averaged data train from said signal, the averaging being performed over one or more time intervals  $\Delta_i$ ; and

- 10 computing an indication of attributes of said materials from the time-domain averaged data train.

2. The method of claim 1 wherein said one or more time intervals  $\Delta_i$  are constant.

3. The method of claim 1 wherein at least two of said one or more time intervals  $\Delta_i$  are different.

- 15 4. The method of claim 2 wherein the following expression is used to construct the time-domain averaged data train:

$$S_{\Delta}(t) = \int_t^{t+\Delta} dt' S(t') / \Delta$$

- 20 where  $S_{\Delta}(t)$  is the provided time-domain signal.

5. The method of claim 1, wherein the interval  $\Delta_i$  is fixed and the time-domain averaged data train is constructed at times  $t = t_0, t_0 + \Delta, t_0 + 2\Delta, \dots, t_0 + N\Delta$ .

- 25 6. The method of claim 1, wherein the time-domain signal is an NMR echo train.

7. The method of claim 6, wherein the step of computing an indication of attributes is performed using inversion of the constructed time-domain averaged data train into  $T_2$  domain.

- 30 8. The method of claim 7, wherein the  $T_2$  distribution is estimated using the following expression

$$S_{\Delta}(t) = \sum_{T_2} \phi(T_2) \exp(-t / T_2) (1 - \exp(-\Delta / T_2)) + Noise$$

where  $\phi(T_2)$  is the porosity corresponding to the exponential decay time  $T_2$ .

35

9. The method of claim 1 further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

10. A method for measuring an indication of attributes of materials containing a fluid state, comprising the steps of:

providing an NMR echo-train indicative of attributes of materials along the borehole;

constructing a time-domain averaged data train from said NMR echo train, the

10 averaging being performed over one or more time intervals  $\Delta_i$ ; and

computing an indication of attributes of said materials from the time-domain averaged data train.

11. The method of claim 10 wherein said one or more time intervals  $\Delta_i$  are constant.

12. The method of claim 10 wherein at least two of said one or more time intervals  $\Delta_i$  are different.

13. The method of claim 10 further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

14. The method of claim 10 wherein the following expression is used to construct the time-domain averaged data train:

$$Echo_{\Delta}(t) = \int_t^{t+\Delta} dt' Echo(t') / \Delta$$

25 where  $Echo_{\Delta}(t)$  is the provided time-domain signal over a time interval  $\Delta_i$ .

15. The method of claim 10, wherein the time interval  $\Delta_i$  is constant and the time-domain averaged data train is constructed at times  $t = t_0, t_0 + \Delta, t_0 + 2\Delta, \dots, t_0 + N\Delta$ .

16. The method of claim 15, wherein the step of computing an indication of attributes is performed using inversion of the constructed time-domain averaged data train into  $T_2$  domain.

17. The method of claim 16, wherein the  $T_2$  distribution is estimated using the following expression

$$Echo_{\Delta}(t) = \sum_{T_2} \phi(T_2) \exp(-t / T_2) (1 - \exp(-\Delta / T_2)) + Noise$$

where  $\phi(T_2)$  is the porosity corresponding to the exponential decay time  $T_2$ .

18. A method for increasing the spatial resolution of NMR logging measurements, comprising the steps of:

5 providing an NMR echo-train indicative of attributes of materials of interest; and  
constructing a time-domain averaged data train from said NMR echo train, the averaging being performed over one or more time intervals  $\Delta_i$ .

19. The method of claim 18 wherein said one or more time intervals  $\Delta_i$  are constant.

10 20. The method of claim 18 wherein at least two of said one or more time intervals  $\Delta_i$  are different.

21. The method of claim 18 further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

15 22. The method of claim 18 wherein the following expression is used to construct the time-domain averaged data train:

$$Echo_{\Delta}(t) = \int_t^{t+\Delta} dt' Echo(t') / \Delta$$

20 where  $Echo_{\Delta}(t)$  is the provided time-domain signal.

23. The method of claim 18 wherein the time interval  $\Delta_i$  is constant and the time-domain averaged data train is constructed at times  $t = t_0, t_0 + \Delta, t_0 + 2\Delta, \dots, t_0 + N\Delta$ .

24. The method of claim 23, wherein the step of computing an indication of  
25 attributes is performed using inversion of the constructed time-domain averaged data train into  $T_2$  domain.

25. The method of claim 24 wherein the  $T_2$  distribution is estimated using the following expression

$$30 \quad Echo_{\Delta}(t) = \sum_{T_2} \phi(T_2) \exp(-t / T_2) (1 - \exp(-\Delta / T_2)) + Noise$$

where  $\phi(T_2)$  is the porosity corresponding to the exponential decay time  $T_2$ .

26 A method for real-time processing of NMR logging signals, comprising the steps of:

providing real-time data corresponding to a single-event NMR echo train indicative of physical properties of materials of interest;

- 5 constructing a time-domain averaged data train from said NMR echo train, the averaging being performed over time interval  $\Delta$  using the expression

$$S_{\Delta}(t) = \int_t^{t+\Delta} dt' S(t') / \Delta$$

- 10 where  $S(t)$  is the provided measurement signal, and the time-domain averaged data train is constructed at times  $t = t_0, t_0 + \Delta, t_0 + 2\Delta, \dots, t_0 + N\Delta$ ; and

computing in real time an indication of the physical properties of said materials based on the constructed time-domain averaged data train.

- 15 27. The method of claim 26, further comprising the step of inverting of the constructed time-domain averaged data train into the  $T_2$  domain, wherein the  $T_2$  distribution is modeled using the expression

$$Echo_{\Delta}(t) = \sum_{T_2} \phi(T_2) \exp(-t / T_2) (1 - \exp(-\Delta / T_2)) + Noise$$

- 20 where  $\phi(T_2)$  is the porosity corresponding to the exponential decay time  $T_2$ .

28. The method of claim 26, further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

25

30

35